

## Prefinished Douglas Fir Flooring Architectural & Design Specifications

MINIMUM ORDER	200 sq.ft.
IMITATION ON BEIN	200 34.11.
SURFACES	Floors, walls & ceilings
SPECIES	Salvaged & Certified Montana Douglas Fir
GRADE QUALITY	99% usable
STABILITY	Fine grain averaging 15 growth rings per inch
HARDNESS	770 Janka Rating
MOISTURE CONTENT	Cured & kiln dried to 6-8% moisture content
THICKNESS	Full 3/4"
WIDTHS	5 1/8", & 7" face coverage
LENGTH	Random lengths up to 8'
GRAIN	Mixed
PROFILE	Micro bevel edges, relief kerfs, clinch line, T&G and end-matched (T&G on the ends)
FINISH	Multi step factory finish including hand rubbed penetrating oils and multiple coats of low/no VOC water based catalyzed floor finish
CERTIFICATION	Salvaged or SFI Certified wood harvested within 100 miles of our facility. LEED eligible based on various criteria including salvaged & locally sourced material
DISTRIBUTION	Factory direct shipping anywhere in the U.S.
PRICING	Call or email square footage and zip code for a delivered price to your project. 406.642.7120 or www.sustainablelumberco.com/contact